

CHIPPERS

These three chippers are the most popular sizes in PTO driven units. The 4" & 5" capacity chippers are gravity fed. The 6" capacity chipper has hydraulic power feed with instant forward, stop, and reverse controls. These chippers are smooth running, compact units that are productive and affordable. Both models are engineered to provide easy access for component maintenance. These chippers are the all-in-one solution for agricultural, landscaping, and property maintenance.



SPECIFICATIONS:

MODEL NO:	418	524	624
Mounting:	Cat. 1, 3-pt	Cat. 1, 3-pt	Cat. 1, 3-pt
Power Source:	PTO	PTO	PTO
Chipping Capacity:	4"	5"	6"
Horsepower Required:	18 - 25 HP	20 - 30 HP	25 - 35 HP
Feed System:	Gravity	Gravity	Hydraulic
Feed Rate:	D.N.A.	D.N.A.	82 ft. per min.
Flywheel:	1"x18" dia.	1 1/4"x24" dia.	1 1/4"x24" dia.
Chipping Knives:	2	2	2
Length:	48"	48"	86"
Width:	34"	42"	44"
Height, Includes Discharge:	75"	75"	78"
Feed Table Height:	40"	42"	42"
Weight:	390#	510#	820#

FEATURES:

- ❑ Units available in Cat. 1, A.S.A.E. 3-point quick hitch
- ❑ Hydraulically powered feed roll for instant forward, stop, and reverse control (624 only)
- ❑ Two full length special "chipper steel" reversible knives
- ❑ Heavy steel flywheel machined from steel plate turns at 1790 RPM
- ❑ Pin to lock flywheel in place when doing blade maintenance
- ❑ The top half of the chipper housing swings open and the belt guard comes off for easy maintenance - all with "no tools"
- ❑ Gap gage with storage location for accurate setting of bed knife
- ❑ Powder coated paint for rust-free durability and glossy finish