



OFFSET DISCS



CAT I
A. S. A. E.
QUICK
HITCH
COMPATIBLE

*Heavy Quick Hitch
Mast On Both Discs*

FEATURES:

- Cat. 1, 3-Point hitch
- 7" Blade spacing
- Triple sealed ball bearings
- Adjustable front and rear gangs
- 1 1/8" Square high carbon axles
- 18" Notched front and plain rear blades

SPECIFICATIONS:

MODEL NUMBER	CUTTING WIDTH	APPROX. H.P. REQUIRED	NO. OF BLADES	WEIGHT
C1218	42"	14 HP	12	375#
C1418	48"	16 HP	14	420#
C1618	54"	18 HP	16	480#
D1818	60"	22 HP	18	620#
D2018	66"	24 HP	20	670#

TANDEM DISCS



CAT I
A. S. A. E.
QUICK
HITCH
COMPATIBLE

FEATURES:

- Cat. 1, 3-Point hitch
- 7" Blade spacing
- Triple sealed ball bearings
- Adjustable front and rear gangs
- 1 1/8" Square high carbon axles
- 18" Notched front and plain rear blades

SPECIFICATIONS:

MODEL NO.	CUTTING WIDTH	APPROX. H.P. REQ'D	NO. OF BLADES	WEIGHT
T1618	60"	18 HP	16	525#
T2018	72"	22 HP	20	630#
T2418	84"	26 HP	24	695#

TANDEM DISCS "MEDIUM DUTY"



FEATURES:

- ❑ Cat. 1, 3-pt. hitch, with 3" square tubing frame, A.S.A.E. Quick Hitch
- ❑ Notched front and plain rear, high carbon blades
- ❑ Heavy cast blade spools
- ❑ Sealed bearings provide superior performance
- ❑ Easy, quick angle adjustments of 16, 30, 44 and 57 degrees

SPECIFICATIONS:

MODEL NUMBER	CUTTING WIDTH	BLADE DIAMETER	NO. OF BLADES	WEIGHT
18-16-CBF	60"	18"	16	760#
20-20-CBF	72"	20"	20	800#
20-24-CBF	84"	20"	24	880#



TANDEM DISCS "HEAVY DUTY"



FEATURES:

- ❑ Cat. 1 & 2, 3-pt. hitch, A.S.A.E. Quick Hitch
- ❑ 3/16" x 22" Notched front and plain rear blades
- ❑ 2" x 4" x 3/16" Main frame and gang beams
- ❑ Easy gang adjustment with special pull handles
- ❑ Front and rear gangs adjustable to 7°, 14° or 21°
- ❑ 1 1/8" High carbon square axles
- ❑ 7 1/2" Long cast spool spacers
- ❑ Self aligning, triple sealed bearings
- ❑ Optional: Bolt-on center mounted shank w/6" sweep



These heavy duty 3-point hitch **Tandem Discs** are excellent for leveling, pulverizing and thoroughly finishing seedbeds. The discs are also great for knocking down weeds. The strong rectangular tube frame is engineered for extra strength. Two main cross beams give the frame additional strength. The 3/16" x 22" blades are notched on the front gangs for better cutting, the rear gangs are smooth to give a leveling finish. The bearings are self aligning and factory lubricated for life.

SPECIFICATIONS:

MODEL NUMBER	CUTTING WIDTH	BLADE DIAMETER	NO. OF BLADES	WEIGHT
V1222	4'	22"	12	1000#
T1622	5' - 6"	22"	16	1100#
T2022	6' - 6"	22"	20	1230#
T2422	7' - 6"	22"	24	1515#
T2822	8' - 6"	22"	28	1660#
T3222	9' - 6"	22"	32	1760#